

# UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. 1320.1015/JDH

First Named Inventor or Application Identifier:

Mirta Mabel FASCI, et al.

Express Mail Label No.

**APPLICATION ELEMENTS**

See MPEP chapter 600 concerning utility patent application contents.

**ADDRESS TO: Assistant Commissioner for Patents**  
**Box Patent Application**  
**Washington, DC 20231**

1. ☒ Fee Transmittal Form
2. ☒ Specification, Claims & Abstract ..... [ Total Pages: 24 ]
3. ☒ Drawing(s) (35 USC 113) ..... [ Total Sheets: 8 ]
4. ☒ Oath or Declaration ..... [ Total Pages: 1 ]
  - a. ☒ Newly executed (original or copy)
  - b. ☐ Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 17 completed)
    - i. ☐ **DELETION OF INVENTOR(S)**  
 Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation by Reference (usable if Box 4b is checked)  
 The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
6. ☐ Microfiche Computer Program (Appendix)
7. ☐ Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
  - a. ☐ Computer Readable Copy
  - b. ☐ Paper Copy (identical to computer copy)
  - c. ☐ Statement verifying identity of above copies

**ACCOMPANYING APPLICATION PARTS**

8. ☐ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) ☐ Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
12. ☒ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
14. ☐ Small Entity Statement(s) ☐ Statement filed in prior application, status still proper and desired.
15. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)
16. ☐ Other:

**17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:**☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: \_\_\_\_/\_\_\_\_**18. CORRESPONDENCE ADDRESS**

STAAS & HALSEY  
 Attn: James D. Halsey, Jr.  
 700 Eleventh Street, N.W., Suite 500  
 Washington, DC 20001

Telephone: (202) 434-1500  
 Facsimile: (202) 434-1501

**NEW APPLICATION  
FEE TRANSMITTAL**

Attorney Docket No.	1320.1015/JDH
Application Number	Unassigned
Filing Date	January 20, 1998

AMOUNT ENCLOSED	\$ 527.00	First Named Inventor	Mirta Mabel FASCI, et al.
-----------------	-----------	----------------------	---------------------------

**FEE CALCULATION** (fees effective 10/01/97)

CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
	TOTAL CLAIMS	32 - 20 =	12	X \$ 22.00 =	\$ 264.00
	INDEPENDENT CLAIMS	1 - 3 =	0	X \$ 82.00 =	0.00
	MULTIPLE DEPENDENT CLAIMS (any number; if applicable)			+ \$270.00 =	0.00
	<b>BASIC FILING FEE</b>				+ 790.00
	Total of above Calculations =				\$ 1,054.00
	Surcharge for late filing fee, Statement or Power of Attorney (\$130.00)				+ 0.00
	Reduction by 50% for filing by small entity (37 CFR 1.9, 1.27 & 1.28).				- 527.00
	<b>TOTAL FILING FEE =</b>				\$ 527.00
	Surcharge for filing non-English language application (\$130.00; 37 CFR 1.52(d))				+ 0.00
	Recordation of Assignment (\$40.00; 37 CFR 1.21(h)(1))				+ 0.00
	<b>TOTAL FEES DUE =</b>				\$ 527.00

**METHOD OF PAYMENT**

- ☒ Check enclosed as payment.
- ☐ Charge "TOTAL FEES DUE" to the Deposit Account No., below.
- ☐ No payment is enclosed and no charges to the Deposit Account are authorized at this time.

**GENERAL AUTHORIZATION**


- ☒ If the above-noted "AMOUNT ENCLOSED" is not correct, the Commissioner is hereby authorized to credit any overpayment or charge any additional fees necessary to:

Deposit Account No. 19-3935

Deposit Account Name STAAS & HALSEY

- ☒ The Commissioner is also authorized to credit any overpayments or charge any additional fees required under 37 CFR 1.16 (filing fees) or 37 CFR 1.17 (processing fees) during the prosecution of this application, including any related application(s) claiming benefit hereof pursuant to 35 USC § 120 (e.g., continuations/divisionals/CIPs under 37 CFR 1.53(b) and/or continuations/divisionals/CPAs under 37 CFR 1.53(b)) to maintain pendency hereof or of any such related application.

**SUBMITTED BY: STAAS & HALSEY**

Typed Name	James D. Halsey, Jr.	Reg. No.	22,729
Signature		Date	January 20, 1998

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

Mirta Mabel FASCI, et al.

Serial No.: NEW

Group Art Unit: UNASSIGNED

Filed: January 9, 1998

Examiner: UNASSIGNED

For: MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR  
MULTIPLE USES

PRELIMINARY AMENDMENT

Assistant Commissioner of Patents  
Washington, D.C. 20231

Sir:

Before examination of the above-identified application,  
please amend the application as follows:

IN THE SPECIFICATION:

Page 1, line 1, change "I-BACKGROUND OF THE INVENTION"  
to --BACKGROUND AND SUMMARY OF INVENTION--.

Page 2, line 12, change "II-ILLUSTRATION" to --BRIEF  
DESCRIPTION OF THE DRAWINGS--.

Page 11, line 2, change "III - MAIN OBJECT" to  
--DESCRIPTION OF THE PREFERRED EMBODIMENTS--

line 12, delete "IV - DESCRIPTION--.

REMARKS

This Preliminary Amendment is submitted to improve the form of the specification as originally-filed.

It is respectfully requested that this Preliminary Amendment be entered in the above-referenced application.

If any further fees are required in connection with the filing of this Preliminary Amendment, please charge same to our Deposit Account No. 19-3935.

Respectfully submitted,

STAAS & HALSEY

By: 

James D. Halsey, Jr.  
Registration No.: 22,729

700 Eleventh Street, N.W.  
Suite 500  
Washington, D.C. 20001  
(202) 434-1500  
Date: January 20, 1998

## I -BACKGROUND OF THE INVENTION

The present utility model refers to a new modular container that can be interconnected, for multiple uses; its aim being to favor the conditions for the reusing of containers, especially of the type produced for its later discard.

As it is public and notorious, in the last decades the whole world has been flooded with products with disposable containers that, although they facilitate their employment and reduce derived operative costs of their recovery, (such as the collection, classification, cleaning, transport and storage, etc.) they constitute, on the other hand, one of humanity's bigger ecological problems since, once used it is not known that to make with them.

The problem is increased when such disposable containers are not structured in biodegradable material; by which its discardal is but the simple transfer of the containers from a place to another, without its raw material being degraded.

Within a wide variety of disposable containers -non degradable - that are known, the plastic bottles are without a doubt those that constitute the biggest volume, following them in order, the metallic cans.

Given that, to give an approximate idea of the quantity of containers that are discarded in the world, it is enough to point out the cans that are discarded in Argentina only, approximately 600 million cans are thrown per year. In the particular case of the city of Buenos Aires and the metropolitan area, during the year 1996 4.500.000 tons of garbage of the most diverse

materials were collected; the plastics composing 15%, particularly under the form of containers.

It is so the final destination of the plastic bottles ends being that of the lands and dumps, as well as those denominated "sanitary fillers", which produces a high proportion of environmental contamination, obstructing pipes and mouths of drainages and, mainly, forming true mantels or strata in all type of lands that do not even serve as effective filler material.

There usually exist three forms for facing the problem of the disposable containers (that are not biodegradable):

1 - The destruction of the containers:

- \* By means of mechanic shredding or crumbling: This process, although it facilitates the volumetric reduction of the containers, does not modify the impossibility of degradation of its material.
- \* By means of its burning: Maybe this process is the less recommended of all, since the combustion of some plastic substances (as PVC, for example), is highly polluting.
- \* By means of the action of chemo-destructive agents: Containers have been tried to be eliminated gathering them in big reservoirs where diverse chemical substances are overturned; but such processes had no acceptance, mainly due to the high operative costs, their limited yield; in certain extent, they are also pollutants (since they generate noxious vapors); and to the fact that, in general, they usually produce a residual material anyway.

2 - The reusing of the containers:

- \* This resource, although useful, is employed in a limited proportion, fundamentally, it depends on the contained product (for example, the reusing of disposable containers is not allowed when foodstuffs and medicinal products are concerned). Also, the packed original product contaminates the new content, and it is not always possible to make the containers hygienic, particularly when they are of a frail structure (as for example, those produced in blowing processes).

### 3 - The recycling of the material of the containers:

- \* This resource is also acceptable, because it constitutes a form of use of the container; but it has several inconveniences: in the first place, because as from its first use it is polluted with diverse substances -inclusive those that constituted its first content - and that, to eliminate them, requires of relatively expensive processes; in second place, because the recycled plastic does not keep the properties of the original raw material and, therefore, it presents diverse practical inconveniences, such as premature aging, a greater fragility, a poor presentation due to the combining of pigments, etc.

Due to the abovementioned, only a minimum proportion of plastic bottles end up being reused, or recycled.

The utility model that is described in the present documentation, constitutes an ingenious resource that facilitates the reusing of disposable containers -such as plastic bottles - with a different utilitarian end.

In essence, it is related to the production of a new type of disposable container -so much in the lateral walls as in the top and bottom parts - provided of means of reciprocal interconnection with other containers of the

same characteristics; so that, instead of throwing them, you can stimulate the accumulation of the empty containers to compose structures of all type and application, such as recreational, functional, ornamental, etc.

In this way, for example, in a constructive aspect, the bottles that can be engaged in the form of modular blocks that can constitute an interesting solution to the housing problem. So that the transparent empty blocks conform panels, or part of the same enabling the light to pass through the same, cooperating with the environmental natural illumination as well as to the saving of energy.

Also, in such an application, if to the modular blocks component of each container reused in this manner are left empty, (containing only air) they constitute a thermo-insulating structure; while if they are filled with sand, earth or another appropriate pulverulent or granulated material, this confers them a greater inertia and, in the event of being used a dark material, may can also retain the heat of the solar rays to offer more comfort to a house during the night.

Similarly, the new containers can be interconnected to form recreational or didactic composition games, - circumstance that is valuable to give opportunity to children and youngsters to develop their genius-, and to contribute to the use of a non pollutant in their environment.

It is foreseen that the connections can be carried out forming structures so much straight as well as uneven, undulant, arched and, even annular segmented.



The engaging among each two consecutive bottles by their top end and by their bottom end , can be carried out with a threaded neck with or without their cover; including, also, said engagings, means of retentive fit that prevent the modular elements from disconnecting spontaneously.

In fact, the new system can be applied in everything that the imagination is able to conceive, returning to Man the capacity to imagine, allowing him to apply his genius in the conception of the most diverse structures and configurations, and to carry them out with his own hands, to transform disposable containers in utilitarian and aesthetic systems. That is to say, to make from the useless and harmful, an innovative and useful employment.

## II - ILLUSTRATION

For better clarity and understanding of the utility model, it has been illustrated with several figures in which it has been represented in one of its favorite embodiments, everything as an illustrative example, not limitative, in which figures indicated with a letter corresponds to a same type of embodiment; being:

Figure 1-A is a view in perspective of the modular container that can be interconnected in which the means of male and female engaging are inlet and outlet in a cylindrical way. It can be seen that the same are disposed in the lateral faces and guided in the longitudinal sense of the container.

Figure 2-A, is a traverse section in perspective of the container, that allows to clearly appreciate how the mentioned male-female engaging means are disposed and conformed starting from the respective walls.

Figure 3-A, is a schematic view in traverse section of two containers in the form of a bottle with circular male-female engagings, indicating how the lateral connection takes place according to the arrow.

Figure 4-A, is a lengthwise view in perspective of the container cut in two, and observed from its bottom or base, to show the conformation of the same, of compatible engaging with the neck, with or without its cover.

Figure 5-A, are two containers cut lengthwise and represented in perspective to show the way in which the end interconnection of the bottles takes place according to the present invention.

Figure 6-A, is a view in perspective of two containers in circumstances of being interconnected by their ends (top and bottom) of reciprocal engaging.

Figure 7-A, is a longitudinal section in perspective of two containers as shown in figure 4-A, already interconnected by the reciprocal rim of the top wall and neck of one in the cavity of the bottom of the other one.

Figure 8-A, is a form of connection of the container according to the embodiment of figure 1-A that shows three interconnected bottles: two of them in a colinear manner by their coupling ends -top and bottom - and the third, forming 90° with the first and second bottles.

Figure 9-A, is another form of connection of the container according to the embodiment of figure 1-A that shows two containers connected in the form of a cross.

Figure 10-A, is another form of connection of the container according to the embodiment of figure 1-A that shows superimposed lines of containers interconnected laterally by its ends and by two of its opposite lateral walls, forming a wall.

Figure 11-A, is another way of connection of the containers according to the embodiment of figure 10-A that shows how two walls formed by containers can be connected and concurrent to an corner area.

Figure. 12-A, is a schematic detail in traverse section and increased scale of a set of engaging reciprocal male-female means between two modular containers; this increased detail of the profile of the sides of reciprocal rim, shows the formation of slots or grooves dedicated on one hand to cooperate with the security of the connection, and on the other part to allow the exit of the air occluded in the female cavity.

It is a lateral view of a container in which the lateral interconnection means are rectangular and they are guided in the traverse sense of said container.

Figure 13-B, is a view of a bottle according to the present invention, but with its means of engaging conformed and disposed according to a new way embodiment in which the same consist in straight and rectangular inlets and outlets that, alternately, extend all along the lateral walls of said container; the top coupling means being disposed and conformed in an identical way as in figures 1 at 12-A.

Figure 14-B, is a schematic traverse section of a plurality of containers conformed according to the embodiment in figure 13-A, showing the way in which the lateral interconnection can take place with the mentioned means.

Figure 15-C, shows a perspective of the bottle according to the reference invention in a new way of embodiment in which the inlet and outlet lateral interconnection, are straight and are transversely disposed.

Figure 16-C, is a perspective of two bottles according to the embodiment of figure 15-C, showing the way in which the mechanical connection takes place among the same by means of straight traversal couplings.

Figure 17-C, is a schematic view in elevation of different bottles interconnected with union, and according to the embodiment of figures 15 and 16-C.

Figure 18-D, is another way of embodiment that, maintaining the basic concepts of top and bottom couplings bottom, as well as the means lateral coupling, in this case it presents the particularity that this lateral coupling means consist on alternate straight projections with straight recesses, of male-female connection, but they are guided sidelong with regard to the longitudinal geometric axis of each lateral wall.

Figure 19-E, is a view in perspective of the container, in which its format has been modified since, instead of the cylindrical or prismatic form is, in this case, of trapeziform traverse section.

Figure 20-E, is a view of the embodiment 19-E of the container, shown in perspective from its top wall, to observe how it can lean on by one of its

faces, for example, the mayor base of the particular trapeziform sectional configuration.

Figure 21-E, is a view of several containers of trapeziform traverse section, interconnected by the lateral coupling means according to the invention, forming an undulant body.

Figure 22-E, is a variant of application of the connected trapeziform containers forming an arch.

Figure 23-E, is another variant of application of the connected trapeziform containers forming a body of straight segments.

Figure 24-E, is another variant of application of the connected trapeziform containers forming a straight structure.

Figure 25, is a detail in section and in an increased scale in relation to that of the previous figures that shows the way in which the longitudinal coupling between two containers -of equal characteristics- takes place -by means of the entrance of the neck -without the cover that is shown here in a dotted line- of one of the containers in the female coupling depression or lid formed in the external cavity of the bottom of the other container; also, in this figure it is clearly observed how the annular indented cord, as from which the neck of the container is born, fits retentively in a compatible ring groove provided by the female cavity of the other container, to assure the positional retention of the coupling.

Figure 26, is a detail of the neck of a container, without its cover, indicating how it is that can be fitted into the annular cord in the compatible groove of the other container; and finally,

Figure 27, the same detail of figure 27 that shows a container with the cover locked in the compatible cavity of the other and positionally locked by the reciprocal rim of the cord and annular groove of said containers.

In the different figures, the same reference numbers indicate same or corresponding parts, and the groups of several elements have been pointed out with letters.

#### **Listing of the main references:**

- (a) means of lateral interconnection of the bottles
- (b) means of top interconnection of the bottles
- (1) lateral walls [those provided by the means]
- (1') lateral wall of minor base (in the embodiment of the trapeziform container, fig. 19 to 24)
- (1'') lateral walls (in the embodiment of the trapeziform container, figures 19 to 24)
- (2) lateral male engagings
- (2') lateral female engagings
- (3) bottom
- (4) top wall
- (4') cavity of the bottom (3) for the top interconnection
- (5) neck of (4), [it acts as male top connector
- (5') top female coupling in the bottom (3)
- (6) lid
- (7) indented annular cord, from the beginning of the neck (5)

(7') annular retentive groove of (7).

### III - MAIN OBJECT

To the specified ends, the new modular container that can be interconnected, for multiple uses, is of the type that, conforming a bottle or similar thing, -of structure and materials usually developed for their disposal -, essentially includes a bottom (3) and lateral walls (1) finished in a top wall (4); and this top wall (4), is prolonged in a neck (5) delimiting an access mouth to its interior, that can be shut by means of a cover (6) that can be removed; characterized because so much the lateral walls (1) as those of the bottom (3) and top (4), possess means of lateral and top interconnection (a) with other containers (A) of the same characteristics.

### IV - DESCRIPTION

In general terms, and as it was already anticipated, the invention refers to a container that essentially can conform a plastic bottle or similar its structure and materials being usually developed for its disposal, after the use of its content. These type of bottles essentially include a bottom (3) in which the lateral walls (1)origin, finishing in a top wall (4) that can be plane, or forming arched shoulders, in form of cone trunk, etc.; being prolonged the same one in a neck (5) that, in form of tubular mouthpiece, it defines an access mouth to the interior of the bottle, that can be shut by means of a cover (6) that can be removed (that can be fit by threading, pressure, etc.).

In the case of the present utility model, the modular bottle that can be interconnected possesses interconnection means (a) and with other containers of the same characteristics.

The interconnection means (a) are disposed in lateral walls (1), while they make it in a combining manner in their bottom (3) and in their top wall (4).

In this way, so much the lateral walls (1) as the top and the bottom of each container possess means of lateral and top interconnection (a),. [See figures 1-A, 4-A, 13-B, 15-C, 18-D]; which allows this type of containers -once they are empty- to be reused with recreational, didactic, functional ends, etc. by means of reciprocal joinings (as for example, those illustrated in figures 3-A, 5-A, 6-A, 7-A, 8-A, 9-A, 1-A, 11-A, 12-A, 14-B, 16-C, 21-E, 22-E, 23-E, and 24-A in a non limitative way).

Essentially, the means of lateral interconnection (a) consist in inlets and outlets conformed in the lateral walls (1) of the bottle as means of lateral engagings male (2) and female (2 ') that are compatible to each other.

In a favorite form of embodiment the mentioned lateral male engagings (2) are constituted by cylindrical salients that constitute coupling buttons compatible with the lateral female engagings (2 ') that are incoming or equally cylindrical cavities. These means of lateral interconnection (a) are disposed in the lateral walls (1) guided in the longitudinal sense of the bottle, and aligned on a same axis and so that the opposite lateral walls (1) have different engagings (2) and (2 '). In this way while a lateral wall (1) has lateral male



engagings (2), the opposite lateral wall (1) -or, in its case, the adjacent one- possesses lateral female engagings (2 '). [See series of figures A].

The employment of male female coupling lateral means (b) in a cylindrical way, besides simplifying the connection, has the advantage of facilitating the relative rotation among pieces connected by a single set of means (2)-(2 '), if it were required to (figure 9-A). But, equally, the salient ones in form of buttons (2) can be polygonal as well as hexagonal, pentagonal, etc.; and should be of the same format compatible with the female coupling means (2 ').

In other embodiments the means of lateral interconnection (a) among bottles can be constituted by lateral male (2) and female (2 ') engagings of different conformation. In this way, the same (2)-(2 ') can be straight alternate inlet and outlet of parallelepiped rectangular configuration, disposed alternately in each lateral wall (1), as observed in the series of figures of the embodiments B, C and D. In different embodiments, these lateral engagings (2)(2 ') can be guided so much in the longitudinal sense of the bottle (figure 13-B and their form of connection 14-B), as well as in the traverse sense (figure 15 to 17-C); and even oblique (figure 18-D).

Preferably, the lateral faces -dedicated to enter in reciprocal contact in the salients (2) and recesses (2 ') - have a slotted or grooved design (like schematized in the section of figure 12-A), with the purpose of offering a greater coupling retention and to facilitate the exit of the air (since, being the same occluded, its pressure would tend to produce the spontaneous disengagement).

With regard to the means (b) of extreme interconnection between the top of a bottle and the bottom of another of the same type, which are those shown in figures 4, 5, 7, 13, 25, 26 and 26. In general, the same consist on a salient in the way of a male coupling, -conformed by the top wall (4) of the bottle-, compatible with a recess that defines the external face of the bottom (3) of the bottle

More particularly, the top wall (4) of the bottle that conforms the shoulders of the same (plane, arched, conical, etc.), toward the proximal extremity of the same container it gradually reduces its traverse section, to finish in the neck (5) that can be threaded or with projections to allow the fit of a cover (6) that can be removed. In a concordant way, the bottom wall (3), by way of a means of female connection with the top wall (4) and its neck (5), conforms a concavity (4 ') of size and format compatible with the mentioned shoulders, also including a central depression compatible with the neck (5) of the bottle; being able to produce the coupling of the mentioned neck (5) in direct form, (figure 25 and 26), or still providing its lid (6), figure 27.

Note that, preferably, it has been foreseen that the neck (5) of the bottle, beginning or possessing a salient or annular cord (7) projected from the periphery of said container and finished in the form of and annular tooth (figures 25 to 27).

This projection can be of the type that usually certain container type has to hold the bottles, as a resistant handle (since the necks are usually relatively short); undoubtedly in this case it is used to fit in an annular groove (7 ') which -compatible in format and disposition with the mentioned cord (7)-

during the coupling that is indicated in figures 25 and 27, this groove works as retentive rim of the coupling, avoiding the component parts to come out, unless forced to it.

In agreement with the mentioned forms, the cavity (4 ') of the bottom wall (3) can be rounded concave, or infundibuliform with a concave portion. In this last case the concave portion can have a trunk-conical form, in a case, or trunk-pyramidal in another. In all the cases the concave portion is provided of a central depression compatible with the neck (5) of the bottle.

In another embodiment form the cavity (4 ') of the concave bottom (3) conforms a female top coupling (5 ') that is in size and shape compatible with the neck (5) of the bottle, without its cover (6). This coupling (5 ') can have nerves or internal projections that define a lightly smaller interior diameter to the exterior of said neck (5), so that the male-female interconnection among the mentioned neck (5) of a bottle, and the coupling (5 ') of the central cavity (4 ') provided by the bottom (3) of another bottle, is able to take place by pressure forced fitting.

In synthesis the union of the modular bottles that can be interconnected by means of their respective lateral male (2) and female (2 ') engagings, as well as by means of their necks (5) and coupling tops (5 ') allows the constitution of groups in diverse ways and applications, from imaginative devices to structural groups as walls. [such as those shown as simple illustrative examples, not limitative, in figures 3-A, 5-A, 6-A, 7-A, 8-A, 9-A, 1-A, 11-A, 12-A, 14-B, 16-C, 21-E, 22-E, 23-E, and 24-A].

In what concerns to the format of the container itself, this can be cylindrical, square prismatic, square octagonal prismatic, hexagonal prismatic(to allow constructions in the shape of "beehives"), etc.; although always maintaining the principle of the lateral and end coupling means which constitutes the essence of the invention.

Another of the possible ways of embodiment of this format -helping to favor the reusing of the bottles up to now discarded - is to give to the same a format of trapeziform traverse section (illustrated in figures 19-E, 20-E, 21-E, 22-E, 23-E and 24-E), defined by the mayor base (1), the minor base(1 ') and the sides (1").

With this form, according to the position in which the sides (1") of the connected bottles are coupled, one may obtain undulant conformations as those of figure 21-E, segmented as in figure 23-E, arched like in 22-E which, completed, can define a complete circle; straight line as in figure 24-E; etc.

In all the cases, the bottles connected in this way, being any its form and the type of the used joining means, allows to build walls or hollow, insulating structures, or filled with diverse materials such as earth, sand, etc.

It is certain that being the present utility model taken into practice, modifications in will be able to be introduced respecting construction and shape details, without it implying to part from the fundamental principles that are clearly substantiated in the claim clauses that follow.

## V - CLAIMS

Being this way especially described and determined the nature of the present utility model, and how it can be taken into practice, it is declared to claim, as of exclusive right and property:

1) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; of the type that, conforming a bottle or similar thing, -of structure and materials usually developed for their disposal -, essentially includes a bottom and lateral walls finished in a top wall; and this top wall, is prolonged in a neck delimiting an access mouth to its interior, that can be shut by means of a cover that can be removed; characterized because so much the lateral walls as those of the bottom and top, possess means of lateral and top interconnection with other containers of the same characteristics, consisting in compatible recesses and salients and of reciprocal fit through pressure

2) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 1, characterized because the means of lateral interconnection are recesses and salients conformed in the lateral walls of the container as male-female engaging means, compatible to each other and disposed along said walls.

3) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 2, characterized because the means of lateral interconnection are guided in the longitudinal sense of the container.

4) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 2, characterized because the means of lateral interconnection are guided in the traverse sense of the container.

5) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 2, characterized because the means of lateral interconnection are guided sidelong with regard to the longitudinal geometric axis of the container.

6) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 2, characterized because the means of lateral interconnection are alternate recesses and salients compatible to each other that constitute male-female engaging means with the equivalent alternate recesses and salients provided by the lateral walls of other containers similar to those with which they are laterally connectable.

7) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 2, characterized because the means of top interconnection are salient conformed in the top wall of the container, compatible with recesses conforming in the bottom an external cavity, as male-female engaging means among said top wall of each bottle with regard to said cavity of the bottom of another container of equal characteristics.

8) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 2, characterized because the compatible salients and their recesses are circular.

9) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 2, characterized because the compatible salients and their recesses are alternate nerves with straight recesses.

10) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 7, characterized because the means of top interconnection of a container -with the cavity and central depression in the bottom of another of equal characteristics- consist on a neck born in the top shoulder of the container, starting from a surrounding cord that is projected forming an annular tooth of retention against an annular groove, compatibly provided by the mentioned cavity of the bottom.

11) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 7, characterized because the top wall of the container, conforming the shoulders of the same, toward the proximal extremity reduces gradually its traverse section, ending forming the neck; while, in a concordant way, the bottom wall -as a female connection means with the top and its neck - affects a cavity of size and format compatible with the mentioned shoulders and that includes a central depression compatible with the admission of the mentioned neck of another container of equal characteristics.

12) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 7, characterized because the shoulders are rounded convex.

13) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 7, characterized because the shoulders are in the form of cone trunk whose smaller base is prolonged conforming the neck of the bottle.

14) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 7, characterized because the shoulders are in trunk-pyramidal shape whose smaller base is prolonged conforming the neck of the container.

15) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 10, characterized because the external cavity of the bottom is rounded concave, and affected of a central depression compatible with the neck of the container; being the adjacency area among the mentioned central depression and said cavity of the bottom, affected of an annular groove compatible with the annular cord of the neck; so that in the rim connector between. lola

16) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 9, characterized because the cavity of the bottom is infundibuliform, with a concave portion in the form of cone trunk provided of a central depression -compatible with the neck of another bottle of the same characteristics- and an annular groove, in turn compatible to the retentive fit of the annular cord of the other compatible bottle which is connectable to the same.

17) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 15, characterized because the



cavity of the bottom is infundibuliform, with a concave portion in a concave trunk-pyramidal shape, provided of a central depression compatible with the neck of the bottle.

18) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 15, characterized because the central cavity of the concave bottom is in size and shape compatible with that of the neck, the annular cord of the bottle and its cover.

19) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 15, characterized because the central cavity of the concave bottom is in size and shape compatible with that of the neck and annular cord of the bottle of the bottle lacking its cover.

20) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 19, characterized because this central cavity of the concave bottom is inwardly provided of a threaded portion compatible with the threaded portion of the neck of the bottle.

21) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 19, characterized because the central cavity of the concave bottom is in size and shape compatible with that of the neck of the bottle without its cover, although with a lightly smaller interior diameter to the exterior of said neck; so that the male-female interconnection among the mentioned neck of a bottle, and the central cavity provided by the bottom of another bottle is able to take place by forced fit through pressure.

22) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 19, characterized because the central cavity of the concave bottom is in size and shape compatible with that of the neck of the bottle without its cover, although provided of nerves that an interior diameter lightly reduced respecting the exterior of said neck; so that the male-female interconnection among the mentioned neck of a bottle, and the central cavity provided by the bottom of another bottle is able to take place due to forced fit by pressure.

23) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 2, characterized because the central cavity of the concave bottom is in size and shape compatible with that of the neck of the bottle with its cover, although provided of nerves that reduce its interior diameter with regard to the external diameter of said cover; so that the male-female interconnection among the mentioned neck and cover of the bottle, and the central cavity provided by the bottom of another bottle is able to take place due to the forced fit by pressure.

24) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 1, characterized because the traverse section of the bottle is squared, defined by the lateral walls provided of the coupling male-female interconnection means with other bottles of equal characteristics.

25) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 1, characterized because the lateral walls of the bottle correspond to a prism.

26) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 1, characterized because the lateral walls of the bottle correspond to a regular prism.

27) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 1, characterized because the lateral walls of the bottle correspond to an irregular prism.

28) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 1, characterized because the lateral walls of the bottle correspond to a prism of square base.

29) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 1, characterized because the lateral walls of the bottle correspond to a prism of square base in an octagonal shape(that is its corners slanted).

30) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 1, characterized because the lateral walls of the bottle correspond to a prism of octagonal base.

31) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 1, characterized because the lateral walls of the bottle correspond to a prism of trapeziform base.

32) MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; in accordance with claim 1, characterized because the lateral walls of the bottle correspond to a prism of circular base.

## ABSTRACT

MODULAR CONTAINERS THAT CAN BE INTERCONNECTED, FOR MULTIPLE USES; of the type that, conforming a bottle or similar thing, -of structure and materials usually developed for their disposal -, essentially includes a bottom and lateral walls finished in a top wall; and this top wall, is prolonged in a neck delimiting an access mouth to its interior, that can be shut by means of a cover that can be removed; characterized because so much the lateral walls as those of the bottom and top, possess means of lateral and top interconnection with other containers of the same characteristics, consisting in compatible recesses and salients and of reciprocal fit through pressure

es de 1979 a 1989

Figura 1 A




Figura 2 A




Figura 3 A




Figura 4 A




Figura 5-A




Figura 8-A

Figura 9-A




Figura 11-A




Figura 10-A




Figura 12-A






Figura 13-B




Figura 14-B




Figura 18 D




Figura 15 C




Figura 16 C




Figura 17C




Figura 19 E




Figura 20 E




Figura 23 E




Figura 22 E

22.5 GRADOS

Figura 24 E





Figura 21 E



## Figura 25




Figura 26<sub>5</sub>





figura 27



## COMBINED DECLARATION/POWER OF ATTORNEY FOR UTILITY/DESIGN PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name. I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled Modular containers that can be interconnected, for multiple uses.

the specification of which (check one) ☐ is attached hereto ☐ was filed on \_\_\_\_\_ as U.S. Application Serial No. \_\_\_\_\_ and was amended on \_\_\_\_\_ (if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose to the Office all information known to me to be material to patentability as defined in §1.56. I hereby claim foreign priority benefit(s) under 35 U.S.C. §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application(s) for patent or inventor's certificate having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

(Number)	(Country)	Day/Month/Year Filed	Priority Claimed <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
M970100488	Argentina	7-February-97	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
_____	_____	_____	<input type="checkbox"/> Yes <input type="checkbox"/> No

I hereby claim the benefit under 35 U.S.C. §120 of any U.S. application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application(s) in the manner provided by the first paragraph of 35 U.S.C. §112, and I acknowledge the duty to disclose to the Office all information known to me to be material to patentability as defined in §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)	(Filing Date)	(Status: patented, pending, abandoned)
_____	_____	_____
_____	_____	_____

## POWER OF ATTORNEY:

As a named inventor, I hereby appoint the following attorneys and agents: James D. Halsey, Jr., 22,729; Harry John Staas, 22,010; David M. Pitcher, 25,908; John C. Garvey, 28,607; J. Randall Beckers, 30,358; James H. Marsh, Jr., 24,533; William F. Herbert, 31,024; Richard A. Gollhofer, 31,106; Mark J. Henry, 36,162; Gene M. Garner II, 34,172; Ilene D. Altman, 36,371; Michael D. Stein, 37,240; Paul I. Kravetz, 35,230; Gerald P. Joyce, III, 37,648; Todd E. Marlette, 35,269; Beverly A. Pawlikowski, 36,404; and William M. Schertler, 35,348 (agent) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. Send correspondence to: STAAS & HALSEY, 700 Eleventh Street, N.W., Suite 500, Washington, D.C., 20001, and direct telephone calls to: (202) 434-1500

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. §1001, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor Mirta Mabel Fasci  
Inventor's Signature Mirta Mabel Fasci Date 12-January-98  
Residence San Martin 686, 7° of. "A" - 1004 Buenos Aires- Argentina  
Citizenship Argentina  
Post Office Address Same as the above

Full name of second joint inventor, if any Luis Orlando de Jesus Pittau  
Second Inventor's Signature Luis Orlando de Jesus Pittau Date 12-January-98  
Residence San Martin 686, 7° "A" - 1004 Buenos Aires - Argentina  
Citizenship Argentina  
Post Office Address Same as the above

(Supply similar information and signature lines for third and subsequent joint inventors.)